Go-Dome™ Weight, Size & Seating Guide

Approximate factory packed shipping weights and seating reference layouts

Packed shipping reference

Weights and bag dimensions below are approximate packed shipping values from the primary factory packing table. Exact weight varies by ring, door and fabric configuration. Confirm shipping dimensions and final packed weight in your order quotation.

Standard dome	Packed weight (kg)	Packed dimensions (cm)	Top height (m)
4 m	28	50 x 40 x 40	2.46
5 m	34	60 x 40 x 50	2.95
6 m	38	60 x 45 x 55	3.46
7 m	52	76 x 45 x 60	3.96
8 m	72	76 x 60 x 60	4.46
9 m	By quotation	By quotation	4.95
10 m	By quotation	By quotation	Confirm configuration

Ringed packed shipping reference

Size	Rings	Packed weight (kg)	Packed dimensions (cm)
5 m	1	37	60 x 40 x 50
5 m	3	58	76 x 55 x 46
6 m	1	42	65 x 40 x 50
6 m	2	44	76 x 56 x 41
6 m	3	58	76 x 55 x 50
7 m	1	54	76 x 48 x 60
7 m	2	60	76 x 60 x 60
7 m	3	75	76 x 60 x 60
8 m	2	78	76 x 56 x 65
8 m	3	85	76 x 65 x 65
8 m	5	105	76 x 76 x 60

Other sizes and ring combinations: request the packed shipping specification for your order.

Seating layouts

Theater layouts use rows facing the projection system; Round layouts use concentric seating. These reference capacities are planning examples, not occupancy approvals. Allow space for equipment, accessible seating, clear exits and local fire-code requirements.

Dome size	Theater (rows)	Round (concentric)
4 m	16	24
5 m	29	40
6 m	44	56

Dome size	Theater (rows)	Round (concentric)
7 m	66	68
8 m	93	112
9 m	138	164
10 m	Request a seating plan	Request a seating plan

A 10 m seating capacity depends on your layout and projection equipment. Ask your distributor for a configuration-specific plan; do not extrapolate occupancy from diameter alone.

Planning your room

- The Standard airlock extends approximately 1.1 m beyond the dome. Allow additional circulation and blower space.
- Standard 4 m and 5 m domes use a 6 ft door; larger Standard domes use a 7 ft door.
- Ring count changes the spring line, packed weight and overall room clearance. Consult the Ringed Selection Guide.
- Geo-Go-Dome™ systems are crated to the ordered frame and enclosure configuration; shipping weights and crate dimensions are quoted per project.

Note: Shipping and layout assistance: info@go-dome.com.