Ringed Go-Dome™

DOME FAMILY · Positive-pressure inflatable with 1 to 5 permanently attached inflated rings

Current catalog product



Ringed Go-Dome™.

Key specifications

Item	Specification
Construction	Standard Go-Dome™ cloth dome raised on a vertical wall of inflated rings
Diameters	4 to 10 m
Ring count	1, 2, 3, 4 or 5 rings (0 rings = Standard dome)
Ring tube	Each ring an inflated tube about 30 cm (1 ft) in diameter (original guidance)
Attachment	Rings permanently attached; cannot be added to an existing Standard dome
Spring line	3 rings: about 0.5 m + 0.9 m. 5 rings: about 0.5 m + 1.5 m (2020 sheet)
Door height	Go-Airlock™ door; 6 ft on 4 and 5 m, 7 ft on larger sizes
Deflation	Each ring has its own rapid-deflation zipper beside the door
Inflation	Same fan inflates door, then rings, then dome; blower bought locally
Portability	Heavier and less portable than Standard; suited to multi-day setups
Use	Indoor use; not recommended or warranted outdoors; no wind rating
Options	Wheelchair Entrance; Digi-Go-Dome™ print or Dome Cover™ (not both)

Ring selection guide (2026 owner guidance)

Rings	Audience and use
0 (Standard)	Young children seated on the floor
1	Upper elementary and older on the floor; adds rigidity and stability
2	Taller middle and high school students on the floor; extra perimeter headroom
3	Small folding chairs
4	Cross-back or taller chairs; adult audiences
5	Central fisheye projector; full hemisphere usable

Seating planning reference (2012 Go-Dome chart for 3 to 5 ring domes; planning only, not an occupancy approval)

Diameter	4 m	5 m	6 m	7 m	8 m	9 m	10 m
Theater rows	16	29	44	66	93	138	On request
Round	24	40	56	68	112	164	On request

Figures are nominal. Your authorized Go-Dome™ distributor confirms the configuration, dimensions and details for your order. On request: ask your distributor for this size or detail.